

**Cable**  
**Link 6 Cables**  
**NEXTSPEED® Link 6 UTP Cable**

# HUBBELL

**Features**

- Sweep Tested from 1-500 MHz
- Guaranteed Headroom Over TIA and ISO Category 6
- Small O.D. allows More Cables per Conduit/Pathway
- Backward Compatible to Category 5e, 5 and 3

**Ordering Information**

Description	Color	Catalog Number	UPC Number
NEXTSPEED® Link 6, 4-Pair, UTP Cable, Riser	White	C6RREW	662620290812

**Listings**

ANSI/TIA/EIA-568-C.2 (Category 6 Component)  
 UL Listed and Tested  
 NEC Article 800 Compliant  
 UL Verified Performance

**Specifications**

Wire	23 AWG Bare Solid Copper
Primary Insulation	CMP: FEP
Primary Insulation	CMR: Polyolefin
Cabling	4 Unshielded Twisted Pairs
Outer Jacket	Low Smoke PVC
Inner Jacket	PVC

**Performance**

Verifications IEEE 802.3af (PoE)

**Applications**

Data Centers: Multi Gigabit Between Devices  
 PoE Applications  
 Bandwidth Intense Processing

**Accessories**

NEXTSPEED Jacks, Category 6 **HXJ6W**  
 NEXTSPEED Patch Panel, Category 6 **P6Exx (xx=Ports)**  
 NEXTSPEED Patch Cords, Category 6 **PCXxx\* (xx=Color) (\*=Standard Length)**

**TRANSMISSION SPECIFICATIONS - Worst Case**

TIA/EIA-568-C.2 Category 6 Compliant; ISO/IEC 11801, 2nd ed. Category 6 Compliant

Freq. (MHz)	Ins. loss (dB/100m)	NEXT (dB/100m)	PSNEXT (dB/100m)	ACR (dB)	PSACR (dB)	ELFEXT (dB)	PSELFEXT (dB)	Return loss (dB)
1	2.2	74.4	72.5	72.2	70.4	67.9	64.9	20.2
4	3.9	65.5	63.4	61.7	59.7	52.7	52.9	23.2
8	5.4	60.8	58.7	55.4	53.2	46.8	46.8	24.6
10	6.2	59.5	57.5	53.4	51.5	44.9	44.9	25.2
16	7.7	56.3	54.4	48.7	46.7	40.5	40.6	25.1
31.25	10.8	51.7	50.0	41.3	39.3	34.8	34.8	23.7
62.5	15.6	47.5	45.5	32.2	30.2	28.9	28.8	21.6
100	19.7	44.5	42.4	24.4	22.6	24.9	24.9	20.2
200	29.2	39.9	37.8	10.7	8.9	18.9	18.8	18.1
250	32.7	38.5	36.4	5.7	3.6	16.9	16.9	17.4
300*	36.5	37.0	35.3	-	-	15.2	15.4	16.9
350*	39.6	36.2	34.2	-	-	13.8	13.8	16.4
400*	43.1	36.5	33.5	-	-	12.9	12.9	15.8
500*	48.8	33.9	31.7	-	-	10.9	10.9	15.1
555*	52.2	33.2	31.2	-	-	9.8	10.0	14.8

\* Frequencies beyond the TIA and ISO requirements are for information only.

